

SPECIFICATIONS

VIDEO

- Displays:** 3 x 17.3" a-Si TFT-LCD Optically Bonded, 1200 nit
- Standards:** H.264, H.265, H.263
Tandberg MXP Interop Only
- Camera Inputs:** 2 Inputs; 1 HDMI 1080p60 and
1 3G-SDI/HD-SDI 1080p60 Level A
- Video Inputs:** 3ea HDMI-CEC 2.0 4Kp30
- Video Outputs:** 3ea HDMI-CEC 2.0 4Kp30
- Encode/Decode:** Video: Full HD 1080p60 Content: 4K 2160p15

AUDIO

- Features:** Hi Quality 20 kHz, AGC, ANR, Active Lip
Synchronization, Echo & Noise Cancellation
- Standards:** G.711, G.722, G.722.1, G.729AB, 64 kbps
128 kbps MPEG4 AAC-LD mono & stereo, OPUS
- Microphones:** Beamforming Array of 3 Built-In Omni-Directional
Condenser Microphone Array
- Audio Input:** Balanced Mic/Line Level In w/ 48V Phantom Power
- Audio Output:** Balanced Line Level Output
- Speaker System:** Built-In Near Field Optimized
- Expansion Mic:** Omni-Directional Wideband Microphone¹
- Headsets:** Up to 4 simultaneously¹



Expansion Mic - Extended Range



Headsets - Secure Private Communications

CAMERA

- Field of View:** 120°
- Motorized PTZ:** 170° Pan/Tilt
5x HD Zoom
- Presets:** 3 Presets – Remote Control
- Image Sensor:** 4K-UHD, 1080p-Full HD, 720p-HD



Wireless Remote

CODEC

- Bandwidth:** Up to 6 Mbps Point-to-Point
- Firewall Traversal:** Cisco Expressway™ H.460.18, H.460.19
- Dual Stream:** H.239 (H.323) Dual Stream
- Wireless Sharing:** Webex Clients, Cisco Proximity Client, & Miracast
- Multipoint Support:**
5-way Embedded SIP/H.323 Transcoded H.239, BFCP (Presentation)
Automatic Continuous Presence Layouts
Encryption and Dual Stream from any Site
- Protocols:** H.323, SIP, and Webex
- Embedded Encryption:** H.323 and SIP Point-to-Point
Standards Based: H.235 v3
AES Auto Key Generation & Exchange
- Network Interface:** Ethernet, Wi-Fi 802.11a/b/g/n/ac, & 2x2 MIMO
- Other Interfaces:** 1x USB A port

INTEGRATED BROADBAND ROUTER¹:

- Wi Fi:** 802.11n, 802.11b/g
- Wi Fi Range:** 500+ feet
- Cellular:** Dual SSID, 4G LTE/3G EVDO Rev A, EVDO, Rev A,
WiMAX, LTE/HSPA+, HSPA+
- GPS:** Built-In incl. NMEA GGA, VTG, and/or RMC
- Management:** LAN or Centralized over WAN

GENERAL

- Dimensions:** 24"H x 20"W x 14.5"D
- Weight:** 90 lbs - 100 lbs²
- Language Support:** Up to 23 Languages
- Power:** 100-240VAC, 50-60Hz, 2.4-2.5A²
- Useful Battery Life:** Approx. 3 Hrs.



¹ Available Option(s)
² Depending on Options