



TRANSMIT, RECEIVE, AND RECORD HD VIDEO AND DATA  
IN REAL-TIME FROM MULTIPLE LOCATIONS

## OVERALL SPECIFICATIONS

### DIMENSIONS

- 25.5 x 24.5 x 14.5"
- 70 lbs.
- Pull handle and casters

### RECORDING

#### ENCODING/STREAMING

- H.264
- RTSP
- Unicast
- Multicast

#### RECORDING

- Multiple encoding rates
- Multiple frame rates
- Optional title and credit slides
- Auto record video conferences

#### ARCHIVES

- Access through web browsers (no client software needed)
- No file size or duration limit (within constraints of hard drive)
- Thumbnail images of files
- Automatic download to USB
- Automatic FTP upload w/ encryption

#### VIDEO-ON-DEMAND (VOD) PLAYER

- Securely browse/play remote archives and streams

#### STORAGE

- Total storage hours will vary based on content data rate and resolution estimated at:
- 22 hours at 5 MB
- 110 hours at 1 MB
- 220 hours at 500 KB
- 44-440 hours - AESOP

#### SECURE KEYCARD AUTOMATION SYS

Actual products may vary in appearance from the images in this product sheet. Images shown are for representational purposes only. These specifications are subject to change without notice, and individual system specifications may vary depending on options. MediaPOINTE is a registered trademark in the U.S. and other countries. Other indicated trademarks are the property of their respective owners. Features listed in this product sheet may require specific software version or enabled option keys.

#### MediaPOINTE, Inc.

667 Rancho Conejo Blvd.  
Newbury Park CA, 91320  
T: 805.480.3700  
F: 805.480.3770  
info@mediapointe.com  
www.mediapointe.com

TAC-CR

## HD CODEC SPECIFICATIONS

### COMMUNICATION PROTOCOLS

- H.323
- IETF SIP

### VIDEO

#### COMPRESSION STANDARD

- H.261
- H.263
- H.263+
- H.264

#### RESOLUTION

- Up to 1080p

#### BIT RATE

- H.323/SIP up to 6 Mbps point to point.

### AUDIO

#### BANDWIDTH & CODING

- G.711
- G.722
- G.722.1
- MPEG4 AAC-LC

#### ECHO CANCELLATION

- Stereo echo-canceling supported
- Noise reduction included
- Automatic gain control included

### INTERFACE

#### VIDEO INPUT

- 2 HDMI
- 1 DVI-I
- 1 analog component (Y/Pb/Pr)
- 1 s-video/composite

### VIDEO OUTPUT

- HDMI (video, audio) RGB
- DVI-I

### AUDIO INPUT

- Mic input x 2 (phantom powered)
- Audio input (MIC/AUX) x 2 (RCA pin, stereo) x 1
- 1 HDMI

### AUDIO OUTPUT

- HDMI (audio, video)
- Line output (RCA pin, stereo)
- REC output (RCA pin, stereo)

### CAMERA CONTROL

#### FAR END CAMERA CONTROL

- H.281

### CONTROL/MAINTENANCE

#### INTERFACE

- RS-232C

### NETWORK

- 10BASE-T/100BASE-TX
- ISDN unit interface

### WIRELESS

- 802.11 b/g

## DISPLAY SPECIFICATIONS

### DIMENSIONS

- 25.5 x 24.5 x 14.5"
- 70 lbs.

### DISPLAY TYPE

- 22" diagonal FHD active matrix LCD with LED BLU back light and optical bonding

### MAXIMUM RESOLUTION

- 1920 x 1080i (true HD)

### HDMI INPUTS

- 1 PC (RGB inputs)
- 1 DVI inputs
- 1 (DVI-D) signal inputs- PC
- 1920 x 1080 max

## CAMERA SPECIFICATIONS

### LENS

- 10x optical zoom, f=5.1 mm (wide) to 51.0 mm (tele), F1.8 to F2.1

### DIGITAL ZOOM

- 20x (200x with optical zoom)

### TILT RANGE

- 9° vert (4.5° up/ 4.5° down)

### HORIZONTAL VIEWING/LENS ANGLE

- 2.9° ~ 54.1°

### WHITE BALANCE

- Auto
- Indoor
- Outdoor
- One-push
- Manual

### BACKLIGHT COMPENSATION

- On/off

### SIGNAL SYSTEM

- HD: 1080/59.94i, 1080/50i, 720/59.94p, 720/50p
- SD: NTSC (crop/squeeze), PAL (crop/squeeze)

### FOCUS SYSTEM

- Full auto (normal AF/interval AF/zoom trigger AF), one-push trigger, manual, infinity, near-limit setting